

YOU WILL BE HEARING FROM US™



Call today.
For more information or
Detailed product specifications,
Call **909 590-5258** Or visit us at <http://csppro.com>

SPECIFICATIONS

	490	468	257
System Type:	8", 2-way Full Range Bass Reflex System	12", 2-way Full Range Bass Reflex System	15", Direct-Radiating Bass Reflex Subwoofer
Frequency Range (-10 dB):	50 Hz - 20 kHz	60 Hz - 20 kHz	40 Hz -
Frequency Range (-3 dB):	65 Hz - 20 kHz	80 Hz - 20 kHz	50 Hz -
Crossover Frequency:	T5r490	T5r368	T5r257
Nominal Dispersion:	90°H x 90°V	90°H x 90°V	-
Dimension (H x W x D):	10.875" x 15.875" x 10.875" 276mm x 403mm x 276mm	19.375" x 14.375" x 13.75" 492mm x 365mm x 349mm	16.88" x 17.5" x 25" 17.25" x 16.625" x 25"
Net Weight:	28.5 lbs (12.7 kg)	37 lbs 16.5 kg)	50 lbs/55 lbs
LF Driver:	1 x 8LV2i	1 x 12LV2i	1 x 12LV2x/15LV2ii
MF / HF Driver:	1 x H452	1 x H452	None
Sensitivity (1w/1m):	97 dB SPL	98 dB SPL	97 dB SPL
Nominal Impedance:	8 ohms	8 ohms	8 ohms
Rated Maximum SPL:	126.5 dB peak, @ 1m	128.8 dB peak, @ 1m	128 dB peak, @ 1m
Power Capacity:	250 watts	300 watts	300 watts
Peak Power Capacity:	1000 watts	1200 watts	1200 watts
Input Connectors:	One two-terminal barrier strip input connectors	One two-terminal barrier strip input connectors	One Speakon +- 1 in parallel
Mounting & Suspension:	None	None	None
Focusy:			



MADE
IN USA.

RS™

SERIES™

LA SERIES™

CLX
SERIES

CD™

P.PA® Professional Power Audio

400
series

Mc Series

The DSP Loudspeaker Management System
Predictable array performance ensures system design flexibility

Csp Professional 5157 Cliffwood Dr., Montclair, CA 91763 Tel: 909 590-5258 Fax: 909 580-8462 Email: info@csppro.com
Csp Professional Member of Paul Audio Inc. © All Rights Reserved.



UPWE™ Special
Black polyurea finish
LVi Woofer Driver
Titanium HF Driver

400

Series
SPECIAL

ALL CSP PRODUCTS MADE IN U.S.A.

