

## K SERIES



**Call today.**  
For more information or  
Detailed product specifications,  
Call **909 590-5258** Or  
visit us at <http://csppro.com>

**YOU WILL BE HEARING FROM US™**



K3  
<http://csppro.com/p/k3.asp>

## SPECIFICATIONS

	K2	K1	K3	K7	K4	K5	K6
System Type:	12", 2-way Full Range Bass Reflex System	15", 2-way Full Range Bass Reflex System	15" x2, 3-way Full Range Bass Reflex System	12" x2, Direct-Radiating Bass-Reflex Subwoofer	8", Multi-way Full Range Bass Reflex System	12", Multi-way Full Range Bass Reflex System	15", Multi-way Full Range Bass Reflex System
Frequency Range (-10 dB):	60 Hz - 20 kHz	55 Hz - 20 kHz	45 Hz - 20 kHz	40 Hz -	55 Hz - 20 kHz	45 Hz - 20 kHz	45 Hz - 20 kHz
Frequency Range (-3 dB):	75 Hz - 20 kHz	65 Hz - 20 kHz	55 Hz - 20 kHz	50 Hz -	60 Hz - 20 kHz	55 Hz - 20 kHz	55 Hz - 20 kHz
Crossover Frequency:	T5rk2 SP DDP™ HF driver protection	T5rk1 SP DDP™ HF driver protection	T5rk3 SP DDP™ HF driver protection	T5rk7	T5rk4 SP DDP™ HF driver protection	T5rk5 SP DDP™ HF driver protection	T5rk6 SP DDP™ HF driver protection
Nominal Dispersion:	70°H x 50°V	70°H x 50°V	90°H x 50°V		90°H x 90°V	90°H x 90°V	90°H x 90°V
Dimension (H x W x D):	22.5" x 14.5" x 14.25" 572mm x 368mm x 362mm	25.125" x 17.25" x 16.4375" 638mm x 438mm x 417mm	33.25" x 26.25" x 18" 845mm x 667mm x 457mm	23.5" x 17.25" x 29.875" 597mm x 438mm x 759mm	15.875" x 10.875" x 10.875" 403mm x 276mm x 276mm	19.375" x 14.375" x 13.75" 492mm x 365mm x 350mm	25.125" x 17.25" x 16.4375" 638mm x 438mm x 417mm
Net Weight:	45 lbs (20 kg)	53 lbs (23.6 kg)	108 lbs (48 kg)	88 lbs (39 kg)	36.5 lbs (16.2 kg)	45 lbs (20 kg)	63 lbs (28 kg)
LF Driver:	1 x 12LV2ii	1 x 15LV2ii	2 x 15LV2ii	2 x 12LV2x	2 x 8LV2x	2 x 12LV2x	2 x 15LV2ii
MF / HF Driver:	1 x H452i	1 x H452i	1 x H450, 1 x PZT		1 x H452i	1 x H452i	1 x 8LV2ii, 1 x H452i
Sensitivity (1w/1m):	98 dB SPL	99 dB SPL	103 dB SPL	98 dB SPL	97 dB SPL	97 dB SPL	97 dB SPL
Nominal Impedance:	8 ohms	8 ohms	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms
Rated Maximum SPL:	128.8 dB peak, @ 1m	131 dB peak, @ 1m	136.8 dB peak, @ 1m	131 dB peak, @ 1m	130 dB peak, @ 1m	131 dB peak, @ 1m	131 dB peak, @ 1m
Power Capacity:	300 watts	375 watts	600 watts	500 watts	500 watts	600 watts	600 watts
Peak Power Capacity:	1200 watts	1500 watts	2400 watts	2000 watts	2000 watts	2400 watts	2400 watts
Input Connectors:	One Speakon +- 1 in parallel	One Speakon +- 1 in parallel	One Speakon +- 1 in parallel	One Speakon +- 1 in parallel	One Speakon +- 1 in parallel	One Speakon +- 1 in parallel	One Speakon +- 1 in parallel
Recommended Amp:	PaulAudio 212	PaulAudio 217	PaulAudio 217	PaulAudio 217	PaulAudio 217	PaulAudio 217	PaulAudio 217
Focusy:							



MADE  
IN USA.

RS™

LA SERIES™

CLX  
SERIES

CD™

P.PA® Professional Power Audio

400  
series

Mc Series

The DSP Loudspeaker Management System  
Predictable array performance ensures system design flexibility

All CSP Product  
100% Factory Quality Control  
100% Factory Speaker Construction  
100% Factory Tested  
5 year Warranty  
Manufactured with Pride in the United States  
UPWE SpecialBlack polyurea finish  
LV Woofer Driver  
Compression HF Driver

Provides high power output  
low distortion  
consistent polar response  
that generate super heavy bass



Shouldered Eye Bolt

TM  
SERIES  
MADE IN USA.

## Damping Speaker Technology

K4	K5	K6
8", Multi-way Full Range Bass Reflex System	12", Multi-way Full Range Bass Reflex System	15", Multi-way Full Range Bass Reflex System
55 Hz - 20 kHz	45 Hz - 20 kHz	45 Hz - 20 kHz
60 Hz - 20 kHz	55 Hz - 20 kHz	55 Hz - 20 kHz
T5rk4 SP DDP™ HF driver protection	T5rk5 SP DDP™ HF driver protection	T5rk6 SP DDP™ HF driver protection
90°H x 90°V	90°H x 90°V	90°H x 90°V
15.875" x 10.875" x 10.875" 403mm x 276mm x 276mm	19.375" x 14.375" x 13.75" 492mm x 365mm x 350mm	25.125" x 17.25" x 16.4375" 638mm x 438mm x 417mm
36.5 lbs (16.2 kg)	45 lbs (20 kg)	63 lbs (28 kg)
2 x 8LV2x	2 x 12LV2x	2 x 15LV2ii
1 x H452i	1 x H452i	1 x 8LV2ii, 1 x H452i
97 dB SPL	97 dB SPL	97 dB SPL
4 ohms	4 ohms	4 ohms
130 dB peak, @ 1m	131 dB peak, @ 1m	131 dB peak, @ 1m
500 watts	600 watts	600 watts
2000 watts	2400 watts	2400 watts
One Speakon +- 1 in parallel	One Speakon +- 1 in parallel	One Speakon +- 1 in parallel
PaulAudio 217	PaulAudio 217	PaulAudio 217

## Great revolutionary invention

ALL CSP PRODUCTS MADE IN USA.

Professional sound for  
sound professionals


## K SERIES

Surprise Again!



	K10
System Type:	8"x2, 2-way Full Range Bass Reflex System
Frequency Range (-10 dB):	50 Hz - 20 kHz
Frequency Range (-3 dB):	60 Hz - 20 kHz
Crossover Frequency:	T5rk10 SP DDP™ HF driver protection
Nominal Dispersion:	90°H x 90°V
Dimension (H x W x D):	23.6" x 9.6" x 12" 600mm x 245mm x 305mm
Net Weight:	43 lbs (19 kg)
LF Driver:	2 x 8LV2ii
MF / HF Driver:	1 x H452i
Sensitivity (1w/1m):	97 dB SPL
Nominal Impedance:	4 ohms
Rated Maximum SPL:	129 dB peak, @ 1m
Power Capacity:	400 watts
Peak Power Capacity:	1600 watts
Input Connectors:	One Speakon +- 1 in parallel
Recommended Amp:	PaulAudio 217

Focusy:



MADE IN U.S.A.