Multi-way sound systems

http://csppro.com/p/k5.asp
100% Factory Quality Control


100% Factory Speaker Construction

100% Factory Tested

5 year Warranty

Manufactured with Pride in the United States

The K5 loudspeaker yields 90 degrees horizontal coverage at 90 degrees vertical





## **SPECIFICATIONS:**

System Type:

Multi-way, Full range, bass Drivers:

ported LF (2 :

LF (2 x Csp 12LV2x) HF (1 x Csp H450)

Frequency Range:

45 Hz - 20 kHz (-10 dB) High Frequency Driver

55 Hz - 20 kHz (+/-3 dB)

Protection: SP DDPJ

Power Capacity:

600 W Average Input Connection:

2400 W Peak Neutrik Speakon in Parallel

Recommended Power

Amplifier: 3/4" MDF wood, UPWEJ
P.PA Series Special black polyurea finish

Sensitivity (1w/1m): Grille:

97 dB 18 gauge perforated steel,

additional powder coated

**Enclosure Hardware:** 

Maximum Output:

131 dB Dimensions (H x W x D):

19.375" x14.375 " x 13.75"

Nominal Impedance: 492 mm x 365 mm x 350 mm

4 Ohms

Weight:

Nominal Dispersion: 45 lbs (20 kg)

90° x 90°

Shipping weight: 48 lbs (21.3 kg)

Crossover: T5rK5

## **APPLICATIONS:**

Sound Reinforcement

Clubs, Karaoke Clubs, Health Clubs

Offices, Classrooms, Meeting Rooms

A/V Systems

Houses of Worship

Sport Facilities

Distributed Systems

## **FEATURES:**

Damping Speaker Technology

High power handling - 600 watts(average) and 2400 watts(peak) power capacity

 $90^{\circ}~x~90^{\circ}$  horn designed for even coverage and smooth response on and off axis

1" Titanium HF Driver

SP DDPJ Distortion Dynamic Protection

The advanced network topology crossover design shapes the frequency response to deliver coherent summation in the crossover region

3/4" MDF wood, UPWEJ Special(Ultrachrome Protecting wood enclosures) black polyurea finish

18 gauge perforated steel, additional powder coated Manufactured with Pride in the United States

Csp Professional

5157 Cliffwood Dr., Montclair, CA 91763 USA

info@csppro.com

All information is Copyright © 2005 Csp

www.csppro.com